



Declaration of Performance

according to Regulation 305/2011 of the EUROPEAN PARLAMENT and of the COUNCIL laying down harmonized conditions for the marketing of construction products

Identify code	ST/T1/1316
Typ	Separator for light liquids Oleopator-Bypass P; SD
Use	Light liquid removal from waste water to protecting drainage systems and surface water
Manufacturer	ACO Industries Tábor s.r.o., Průmyslová 1158, 39101 Sezimovo Ústí
Attestation of conformity system	System 4: The manufacturer has discovered the type of product according to the system 4 based of type testing, type calculation, tabulated values (or documentation of the product) and carried out factory-owned production control.
Attestation of conformity system reaction to fire	System 3: The notified agency "PAVUS" (NB Nr. 1391) conducted tests on reaction to fire of the PE materials (protocols No. PK1-01-18-070-E-0 and PK-01-18-071-E-0)


The separator for light liquids is built in accordance to the Construction Products Directive 305/2011/EWG.

The following harmonized standards in the current version at the date of issue have been applied:


DIN EN 858-1:2005	Separator systems for light liquids – part 1: construction, performance and testing, marking and quality control
DIN EN 858-2:2003	Separator systems for light liquids – part 2: selection of nominal size, installation, operation and maintenance
DIN EN 13501-1:2007	Classification of construction products and building their fire behavior – part 1: classification using test data from reaction to fire performance of construction products

Main features	DIN EN 858-1	Performance
Reaction to fire	6.2.8	E
Fluid resistant	6.3.2	pass
Effectiveness	5, 6.3.1, 6.3.3-6.3.8, 6.5	pass
Capacity	6.4	pass
Durability	6.2	pass

Signed for and on behalf of the manufacturer.
Sezimovo Ústí, 20 November 2018


Libor Dočekal (R&D manager)

Information accompanying the CE marking


<p>ACO Industries Tábor s.r.o. Průmyslová 1158 39101 Sezimovo Ústí</p>
<p>11</p>
<p>EN 858-1:2005</p> <p>separator systems for light liquids Oleopass P class I with integrated sludge trap</p> <p>Material: PE-HD Installation parts: PE-HD</p>

Overview of the CE marked separator systems for light liquids
Typ Oleopass P

NS	Sludge trap- volume (l)	Oil storage capacity (l)	Size (mm)
3	450	240	1320
3	670	240	1320
3	950	240	1320
6	660	235	1320
6	1210	235	1320
8	810	260	1320
10	1080	260	1320